

LÚČOVÉ TRYSKY

PARAMETRE

- Nastaviteľná výšec 25° - 360°
- V ponuke 2 možnosti nastavenia dostreku
- Nižšia rýchlosť zavlažovania zabraňuje stekaniu
- Viac lúčov pre rovnomernejšie pokrytie

CHARAKTERISTIKA SPRAYOVÝCH TRYSIEK S-8A

Výšec	Tlak		Dostrek m	Prietok		Zráž. v. mm/h	
	bar	kPa		m ³ /h	l/min	■	▲
90° 	1,0	100	2,1	0,05	0,9	52	60
	1,5	150	2,2	0,07	1,1	55	64
	2,0	200	2,4	0,08	1,4	57	66
	2,1	210	2,4	0,09	1,4	57	66
	2,5	250	2,6	0,10	1,6	58	67
180° 	1,0	100	2,1	0,12	1,9	55	63
	1,5	150	2,2	0,13	2,1	51	58
	2,0	200	2,4	0,14	2,3	47	54
	2,1	210	2,4	0,14	2,3	46	53
	2,5	250	2,6	0,15	2,4	44	50
360° 	1,0	100	2,1	0,24	4,0	56	65
	1,5	150	2,2	0,25	4,2	50	58
	2,0	200	2,4	0,26	4,4	45	52
	2,1	210	2,4	0,26	4,4	44	51
	2,5	250	2,6	0,27	4,6	41	47

Tučné písmo = Odporúčaný tlak

CHARAKTERISTIKA SPRAYOVÝCH TRYSIEK S-16A

Výšec	Tlak		Dostrek m	Prietok		Zráž. v. mm/h	
	bar	kPa		m ³ /h	l/min	■	▲
90° 	1,0	100	4,3	0,08	1,4	18	21
	1,5	150	4,6	0,10	1,6	18	21
	2,0	200	5,0	0,11	1,9	18	21
	2,1	210	5,0	0,11	1,9	18	21
	2,5	250	5,3	0,13	2,1	18	21
180° 	1,0	100	4,3	0,14	2,3	14	17
	1,5	150	4,6	0,17	2,8	15	18
	2,0	200	5,0	0,20	3,3	16	18
	2,1	210	5,0	0,20	3,4	16	19
	2,5	250	5,3	0,23	3,8	16	19
360° 	1,0	100	4,3	0,23	3,9	12	14
	1,5	150	4,6	0,30	5,0	14	16
	2,0	200	5,0	0,36	6,1	15	17
	2,1	210	5,0	0,38	6,3	15	17
	2,5	250	5,3	0,43	7,2	16	18

Tučné písmo = Odporúčaný tlak

LÚČOVÉ TRYSKY



S-8A

Dostrek: 2,1 m až 2,6 m



S-16A

Dostrek: 4,3 m až 5,3 m

S-8A

